

**AAMA/WDMA/CSA  
101/I.S.2/A440-05**

# **Standard/Specification for windows, doors, and unit skylights**

*Reprinted May 2007. This reprint incorporates replacement pages issued as Update No. 1 (March 2007) into the original 2005 Standard.*



# Contents

Preface *vii*

Foreword *ix*

## **0 Introduction** 1

- 0.1 General 1
  - 0.1.1 Applicability 1
  - 0.1.2 Content 1
- 0.2 Performance classes and levels 2
  - 0.2.1 Performance classes 2
  - 0.2.2 For the specifier 2
  - 0.2.3 Performance grade designations 2
  - 0.2.4 Side-hinged door systems 2
  - 0.2.5 Positive and negative design pressure 3
  - 0.2.6 Water penetration resistance testing and performance 4
  - 0.2.7 Operation/cycling performance 5
- 0.3 Short-form specification 5

## **1 Scope** 6

- 1.1 General 6
- 1.2 Terminology 7
- 1.3 Units of measurement 7

## **2 Reference publications** 7

## **3 Definitions** 17

## **4 General requirements** 27

- 4.1 General 27
- 4.2 Markings/identifications 27
- 4.3 Gateway performance requirements 27
- 4.4 Product designations 28
  - 4.4.1 General 28
  - 4.4.2 Primary designator 28
  - 4.4.3 Secondary designator 39
- 4.5 Dual windows or dual doors 42
  - 4.5.1 General 42
  - 4.5.2 Requirements 42

## **5 Testing** 44

- 5.1 Testing sequence 44
- 5.2 Test specimen requirements 44
  - 5.2.1 General 44
  - 5.2.2 Composite units and combination assemblies 44
  - 5.2.3 Alterations 45
  - 5.2.4 Specimen size 45
  - 5.2.5 Installation methods 45
- 5.3 Testing methods 47
  - 5.3.1 Operating force and force to latch 47
  - 5.3.2 Air leakage resistance test 52
  - 5.3.3 Water penetration resistance test 53

- 5.3.4 Uniform load tests 54
- 5.3.5 Forced-entry resistance test 55
- 5.3.6 Auxiliary (durability) tests 56
- 5.3.7 Condensation resistance (optional) 73
- 5.3.8 Thermal transmittance (optional) 73
- 5.3.9 Acoustical performance (optional) 74
- 5.3.10 Impact performance (optional) 74
- 5.4 Laboratory test report 74

## **6 Materials 77**

- 6.1 Material tolerance 77
- 6.2 Glazing and glass 77
  - 6.2.1 Reference Standards 77
  - 6.2.2 General requirements 77
  - 6.2.3 Glazing selection 77
  - 6.2.4 Removable multiple glazing panels 81
  - 6.2.5 Plastic glazing 81
- △ 6.3 Framing/cladding materials 82A
  - △ 6.3.1 General 82A
  - 6.3.2 Wood 83
  - 6.3.3 Flush and molded wood fiber doors 83
  - 6.3.4 Vinyl 84
  - 6.3.5 Cellular PVC 84
  - 6.3.6 Aluminum 84
  - 6.3.7 Fiberglass 85
  - 6.3.8 Steel 86
  - 6.3.9 Cellulosic composite materials 86
  - 6.3.10 Fiber-reinforced PVC 86
  - 6.3.11 Acrylonitrile-butadiene-styrene (ABS) 87
  - 6.3.12 Doorlite insert frame materials 87
  - 6.3.13 Other materials 87

## **7 Components 88**

- 7.1 Hardware 88
  - 7.1.1 General 88
  - 7.1.2 Hung window hardware 88
  - 7.1.3 Casement, awning, hopper, and projected window hardware 88
  - 7.1.4 Door hardware 88
  - 7.1.5 Hinged window hardware 89
  - 7.1.6 Tropical window hardware 89
  - 7.1.7 Dual-action window hardware 90
- 7.2 Fasteners 90
- 7.3 Reinforcing 91
- 7.4 Weatherstrip 91
- 7.5 Insect screens 91
- 7.6 Sealants 91
- 7.7 Coatings/finishes 91
- 7.8 Mullions 92
  - 7.8.1 Mullion rating 92
  - 7.8.2 Composite units 97
  - 7.8.3 Combination assemblies 97
  - 7.8.4 Field mulling without manufacturer's involvement 97
  - 7.8.5 Windload deflection 97
  - 7.8.6 Operational interference 98

- 7.8.7 Vertical (dead load) deflection 98
- 7.9 Integral ventilating systems/devices 98
- 7.10 Blinds in dual-glazed products 98
- 7.11 Setting blocks 98
- 7.12 Dividers (muntins) 99
  - 7.12.1 True divided lites 99
  - 7.12.2 Simulated divided lites, removable grids, and grills 99

## **8 Fenestration type and test size 100**

- 8.1 General 100
- 8.2 Product dimensions and tolerances 100
  - 8.2.1 Dimensions 100
  - 8.2.2 Tolerances 101
- 8.3 Qualification of designs, configurations, and assemblies 102
  - 8.3.1 General 102
  - 8.3.2 Geometry and components 102
  - 8.3.3 Operation and orientation 102
  - 8.3.4 Composite units and unique framing members 103
- 8.4 Specialty products, basement windows, hinged windows, side lites, and transoms 107
  - 8.4.1 Specialty products 107
  - 8.4.2 Basement windows 108
  - 8.4.3 Hinged windows 108
  - 8.4.4 Side lites and transoms 108

## **Annexes**

- A** (informative) — Contact information for standards development organizations 116

---

## **Tables**

- 1** — Gateway requirements 27
- 2** — Product types 31
- 3** — Optional performance grades (design pressure) 38
- 4** — Canadian (only) operating force requirements 48
- 5** — U.S. operating force requirements 50
- 6** — Maximum allowable air leakage 52
- 7** — Canadian (only) air infiltration/exfiltration levels 52
- 8** — Deflection limits for sash/leaf torsion test 59
- 9** — Deflection limits for sash vertical deflection test 60
- 10** — Deflection limits for sash/leaf concentrated load test on latch rail 63
- 11** — Deflection limits for vertical concentrated load test 64
- 12** — Deflection limit for vertical concentrated load test on intermediate frame rails 66
- 13** — Loads for distributed load test 67
- 14** — Loads for stabilizing arm load test 68
- 15** — Load for balance arm load test 69
- 16** — Load for hold-open arm/stay bar test 69
- 17** — Deflection limits for sash blocked operation test 71
- 18** — Operation/cycling performance (side-hinged door systems) 73
- 19** — Allowable glass loads for Examples 1 and 2 in Clause 6.2.3.3 79
- 20** — Plastic glazing combustibility classes 82
- 21** — Door hardware reference Standards 89
- 22** — Requirements for fasteners and reinforcing 90
- 23** — Requirements for finishes 92
- 24** — Window assembly qualification 106
- 25** — Gateway performance requirements 109

## Figures

- 1** — Short-form specification 6
- 2** — Primary designator (Example 1) 28
- 3** — Primary designator (Example 2) 29
- 4** — Primary designator (Example 3) 30
- 5** — Product type illustrations 32
- 6** — Examples of specialty products 35
- 7** — Secondary designator (Example 1) 41
- 8** — Secondary designator (Example 2) 41
- 9** — Secondary designator (Example 3) 42
- 10** — Corner sealant detail 45
- 11** — Test specimen mounting 46
- 12** — Set-up for thermoplastic corner weld test 57
- 13** — Set-up for sash/leaf torsion test 58
- 14** — Set-up for sash vertical deflection test 60
- 15** — Perpendicular load for sash/leaf concentrated load test on latch rail 61
- 16** — Parallel load for sash/leaf concentrated load test on latch rail 62
- 17** — Set-up for vertical concentrated load test 64
- 18** — Set-up for vertical concentrated load test on intermediate frame rails 65
- 19** — Set-up for distributed load test 66
- 20** — Set-up for stabilizing arm load test 67
- 21** — Set-up for balance arm load test 68
- 22** — Set-up for hold-open arm/stay bar test 69
- 23** — Set-up for awning, hopper, projected hardware load test 70
- 24** — Set-up for unit dead load test 72
- 25** — Test report summary of results 75
- 26** — Mullion types and applications 93
- 27** — Product dimension measurement 101
- 28** — Window assembly qualification — Typical configurations 104
- 29** — Side-hinged door assembly qualification 107